

P1157E-500

15" XGA TFT Expandable Industrial Touch Panel Computer with 7th/6th Gen Intel® Core™ i7/i5/i3, Celeron® & Pentium® Processor and PCI/PCIe Slot



- 2. SATA status LED
- 3. Brightness-
- 4. Brightness +
- 5. Display monitor ON/OFF
- 6. Volume-
- 7. Volume +





 1. 1 x Line-out
 9. 1 x RS-232

 2. 1 x RS-232
 10. 4 x USB 3.0

 3. 2 x LAN
 11. 1 x VGA

 4. 1 x RS-232
 12. 1 x DisplayPort

 5. PCle x4 slot
 13. 1 x HDMI

 6. AC plug
 14. 2 x USB 2.0

7. 1 x Mic-in 15. Remote power switch 8. 1 x RS-232/422/485 16. Switch for power on/off

Features

- 15" XGA TFT LCD display
- LGA1151 socket 7th/6th gen Intel® Core™ i7/i5/i3, Celeron® & Pentium® processors
- Intel® H110 chipset
- Less screw design for easy installation
- 4 USB 3.0. 2 USB 2.0 and 4 COM
- One PCIe x4 slot
- Built-in speakers and optional Wi-Fi 802.11 b/g/n module
- Robust IP65 compliant aluminum front bezel
- Supports 5 OSD keys in front panel











Introduction

The P1157E-500 is a multimedia 15" touch panel PC for kiosk application. It has a fashionable mechanism design and industrial-grade material front bezel which can avoid damage from chemical corrosion. To meet the demands of multimedia application, the P1157E-500 is powered by a high performance LGA1151 socket 7th/6th generation Intel® Core™ processor with the Intel® H110 chipset. It features four COM ports, two Gigabit Ethernet and up to 32GB memory of dual-channel DDR4-2133 that delivers high computing capability for high performance-demanding applications. The industrial touch panel PC is most suitable for kiosk, factory and automation.

Expandable for 1 PCIe

The P1157E-500 has one PCle x4 slot for expansion purpose. User can easily plug in standard half-size PCle card based on any application needs.

Speaker and WLAN Antenna Supported

The P1157E-500 features built-in speakers for kiosk application to display multimedia content program. It also supports WLAN module antenna (optional) for wireless network connectivity.

Friendly Less Screw Design

The P1157E-500 is designed with easy of maintenance in mind. There are only four screws on the back chassis, so that technicians can quickly remove the system's back cover with minimum effort.



Specifications

Front Bezel	Aluminum w/ IP65/NEM/	A 4 rugged protection	
LCD Panel Main System	Display Type	15" XGA TFT LCD	
	Brightness	250 nits	
	Resolution	1024 x 768 pixels	
	Viewing Angle	160°/140°	
	CPU	LGA1151 socket 7th/6th gen Intel® Core™ i7/i5/i3, Celeron® & Pentium® processor	
	Chipset	Intel® H110	
	System Memory	2 x 288-pin DDR4-2133 Long-DIMM, up to 32GB	
	BIOS	AMI UEFI BIOS	
	Storage	1 x 3.5" or 1 x 2.5" SATA HDD (9.5 mm height)	
	Drive	N/A	
	Watchdog Timer	255 levels, 1 to 255 sec.	
IO Connector	3 x RS-232		
	1 x RS-232/422/485		
	1 x HDMI		
	1 x VGA		
	1 x DisplayPort		
	4 x USB 3.0 2 x USB 2.0		
	2 x 10/100/1000 Mbps Ethernet (Intel® i219-LM/i211-AT)		
	1 x Audio (Mic-in & Line-out)		
	1 x Remote power switch		
TPM	N/A		
Expansion Interface	1 x PCle x4		
Touchscreen	Projected capacitive multi-touch		
Power Supply	100 to 240 VAC, 200W		
Power Consumption	97.6W		
Dimensions	378.3 mm (14.89") (W) x 90 mm (3.54") (D) x 310.3 mm (12.22") (H)		
Packing Dimensions	510 mm (20.08") (W) x 186 mm (7.32") (D) x 532 mm (20.94") (H)		
Weight (net/gross)	5.4 kg (11.90 lb)/7.8 kg (17.20 lb)		
Operating temperature	0°C to +50°C (+32°F to +122°F)		
Relative humidity	10% to 90% @ +40°C, non-considering		
Operating vibration	1.0G, 5- 500 Hz, random		
	CE		

Ordering Information

w/PCle x4 (P/N: E221157122)

P1157E-500-N-US PCT 15" XGA expandable industrial touch panel computer with LGA1151 socket 7th/6th gen Intel® Core™ i7/i5/i3, Pentium® & Celeron® processor, PCAP touch screen, PCIe x4 slot, 100 to 240 VAC with US power cord

Packing List

1 x P1157E-500

1 x Panel mount kit

1 x US power cord

^{*} Other configuration by request

^{*} Specification and certifications may vary based on different requirements

Optional Accessories

Wi-Fi kit			
P1157E-500 2.5" slir	n HDD kit		
881211572A0E	P1157E-500 rack mount kit		
881211575A0E	VESA & wall mount kit		
E981604011	ATC10 (VESA arm clamp type)		
E981604012	ATW10 (VESA arm wall mount)		
E226171119	Stand kit		
59403200B00E	Remote power switch cable (100 cm)		

Optional OS Installation

Skylake	Windows® 7
	Windows® 8.1
	Windows® 10
Kaby Lake	Windows® 10

Dimensions

