


AIE500-901-FL

Fanless Edge AI System with NVIDIA® Jetson™ TX2 Series, HDMI, 2 GbE LAN, 2 USB, 2 COM or 2 CAN, and 12 or 24 VDC



Features

- NNVIDIA® Jetson™ TX2 with 256-core NVIDIA Pascal™ GPU
- High-performance AI computing for GPU-accelerated processing
- Ideal for intelligent edge applications, machine learning, and computer vision
- Supports M.2 PCIe, SATA SSD, and MicroSD slots
- Supports 2 USB and 2 COM or 2 CAN
- Wide operating temperature from -30°C to +60°C
- Supports JetPack

NVIDIA® Jetson™ TX2 will be available until 2025*
The official end of life notice will be sent at least 8 months before the last shipment.



Specifications

Standard Color	Silver
Construction	Aluminum extrusion and heavy-duty steel, IP40
AI Accelerator	NVIDIA® Jetson™ TX2
CPU	HMP Dual Denver 2/2 MB L2 + Quad ARM® A57/2 MB L2
GPU	256-core NVIDIA Pascal™ GPU
System Memory	8GB 128-bit LPDDR4@1866 MHz onboard
Carrier Board	SBC87901
System I/O Outlet	1 x HDMI 2.0 with 4K2K supported 2 x 10/100/1000 Mbps Ethernet (NVIDIA® + Intel® i210-IT) 2 x USB 3.1 Gen1 1 x Micro USB 2 x RS-232 default (or 2 x CAN by jumper settings) 1 x Recovery switch 1 x Reset button 1 x Power button 1 x 12 or 24 VDC power input connector 4 x SMA-type antenna connector
Watchdog Timer	Built-in TX2
Storage	Onboard 32GB eMMC (via Jetson™ TX2 8GB) 1 x M.2 Key M 2280 with PCIe x1 and SATA SSD slot 1 x Micro SD slot *The bootable device is supported by eMMC only
Wireless Module	802.11ac WLAN, Bluetooth onboard (TX2 8GB only)
Expansion Interface	1 x Full-size PCI Express Mini Card slot (USB + PCI Express signal) *Either Mini PCIe connector or Micro USB (select by recovery switch) 1 x SIM slot
System Indicator	1 x Green LED for system power-on 1 x Yellow LED for M.2 storage
Power Supply	12 or 24 VDC

Specifications

Operating Temperature	-30°C to +60°C (-22°F to +140°F)
Humidity	10%- 95%, non-condensing
Vibration Endurance	3 Grms with M.2 (5 to 500Hz, X, Y, Z directions)
Dimensions	171 mm (6.73") (W) x 110 mm (4.33") (D) x 57 mm (2.24") (H)
Weight (net/gross)	1.2 kg (2.64 lb)/1.7 kg (3.75 lb)
Certifications	CE, FCC Class A
OS Support	Linux Ubuntu 18.04

Packing List

1 x Terminal block connector
1 x Screw pack
4 x Foot pad
2 x Antennas for WLAN (TX2 8GB only)

Power Protection

DC Adapter

OVP (over voltage protection)
OCP (over current protection)

Ordering Information

Standard

AIE500-901-FL	Fanless edge AI system with NVIDIA® Jetson™ TX2 series SoM, 1 HDMI 2.0, 2 GbE LAN, 2 USB, 2 COM or 2 CAN, and 12 or 24 VDC
---------------	--

Optional

8817H5003A0E	Wall mount kit
8817H5001A0E	VESA arm kit
8817H5002A0E	DIN-rail kit
50956A24040E	12V, 36W adapter
M.2 NVMe SSD 128GB or above	
M.2 SATA SSD 128GB or above	
LTE module	
power cord	

* Specifications and certifications may vary based on different requirements.

Dimensions

