

IPGS-5408GSFP

8 10/100/1000T PoE at/af + 4 1000M SFP L2+ Industrial Managed Ethernet

Switch w/ Enhanced G.8032 Ring

- Support IEEE802.3at/af up to 30W per port
- PoE management incl. Detection and Scheduling
- Enhanced G.8032 ring protection < 20ms for single ring. Supports auto mode, enhanced mode, train mode, multi-VLAN and basic mode; Enhanced G.8032 ring covers multicast packets; MSTP 16MSTI /RSTP ; support MRP ring
- Miss-wiring avoidance & node failure protection
- User friendly UI, including auto topology drawing and DDM threshold monitoring with dB values***; Complete CLI
- Support LACP link aggregation, IGMP v3/router port, MLD snooping, DHCP server & DHCP Option82; Port based DHCP distribution, Mac based DHCP server, DHCP Snooping; QoS by VLAN, SSH v2/SSL, HTTPS, INGRESS/EGRESS ACL L2/L3, TACACS+**, QinQ
- Protocol based VLAN; IPv4 Subnet based VLAN
- Optional Environmental Monitoring** for temp., voltage, current, and total PoE load(-M model)
- USB port to backup, restore the configuration file and upgrade firmware*



-E model

Standard model



OVERVIEW

Lantech IPGS-5408GSFP is a high performance L2+ (Gigabit uplink) switch with 8 10/100/1000T + 4 1000M SFP w/8 PoE 802.3at/at Injectors which provides L2 wire speed and advanced security function for network aggregation deployment. It delivers ITU G.8032 enhanced ring recovery less than 20ms in single ring while also supports train ring, enhanced mode, multiple VLAN mode with easy configuration. The comprehensive QoS, QoS by VLAN, advanced security including INGRESS/EGRESS ACL L2/L3, TACACS+**, SSH v2/SSL, Mac based DHCP server, DHCP Option 82, DHCP server, IGMPv1/v2/v3/router port, QinQ are supported and also required in large network. It also supports Cisco Discovery Protocol (CDP) for Ciscoworks to detect the switch info and show on L2 map topology.

Up to 8 PoE at/af ports w/advanced PoE management

Compliant with 802.3at/af standard, the Lantech IPGS-5408GSFP is able to feed each PoE port up to 30 Watts@54 VDC providing the connected PD devices. Lantech IPGS-5408GSFP supports advanced PoE management including PoE detection and scheduling. PoE detection can detect if the connected PD hangs then restart the PD; PoE scheduling is to allow pre-set power feeding schedule upon routine time table. Each PoE ports can be Enabled/disabled, get the voltage, current, Watt, and temperature info displayed on WebUI.

Miss-wiring avoidance, Node Failure protection, Loop

protection

The IPGS-5408GSFP also embedded several features for stronger and reliable network protection in an easy and intuitive way. When the pre-set ring configuration failed or looped by miss-wiring, Lantech IPGS-5408GSFP is able to alert with the LED indicator and disable ring automatically. Node failure protection ensures the switches in a ring to survive after power breakout is back. The status can be shown in NMS when each switch is back. Loop protection is also available to prevent the generation of broadcast storm when a dumb switch is inserted in a closed loop connection.

DHCP option 82 & Port based, Mac based DHCP, Option66, DHCP Snooping; IPv6 DHCP server

DHCP server can assign dedicated IP address by MAC or by port (Port based for single switch), it also can assign IP address by port for multiple switches with single DHCP option82 server. DHCP Snooping is supported. For the ending device which need to download file from TFTP server, DHCP Option66 server can offer IP address of TFTP server to DHCP client. Basic IPv6 DHCP service can be supported.

Auto-provisioning for firmware/configuration update

The switch supports auto-provisioning for switch to auto-check the latest software image and configuration through TFTP server.

User friendly GUI, Auto topology drawing

The user friendly UI, innovative auto topology drawing and topology demo makes IPGS-5408GSFP much easier to get hands-on. The complete CLI enables professional engineer to configure setting by command line.

Enhanced G.8032 ring, 16 MSTI MSTP; MRP ring

Lantech IPGS-5408GSFP features enhanced G.8032 ring which can be self-healed in less than 20ms for single ring topology protection covering Multicast packets. It also supports various ring topologies that covers double ring, multiple-VLAN ring and auto-ring by easy setup than others. The innovative auto-Ring configurator (auto mode) can calculate owner and neighbor in one step. It supports MSTP that allows each spanning tree for each VLAN for redundant links with 16 MSTI.

MRP (Media Redundancy Protocol) can be supported for industrial automation networks.

Editable configuration file; USB port for configuration upload & download

The configuration file of Lantech IPGS-5408GSFP can be exported and edited with word processor for the other switches configuration with ease. The factory reset button can restore the setting back to factory default and built-in watchdog design can automatically reboot the switch when CPU is found dead.

The built-in USB port can have configuration upload & download by USB dongle.

QoS by VLAN for legacy device

QoS by VLAN can allow switch to tag QoS by VLAN regardless the devices acknowledge QoS or not in which greatly enhance the bandwidth management in a network.

QinQ, QoS and GVRP supported

It supports the QinQ, QoS and GVRP for large VLAN segmentation.

IGMPv3, GMRP, router port, MLD Snooping, static multicast forwarding and multicast Ring protection

The unique multicast protection under enhanced G.8032 ring can offer immediate self-recovery instead of waiting for IGMP table timeout. It also supports IGMPv3, GMRP, router port, MLD snooping and static multicast forwarding binding by ports for video surveillance application.

802.1X security by MAC address

MAC-based port authentication is an alternative approach to 802.1x for authenticating hosts connected to a port. By authenticating based on the host's source MAC address, the host is not required to run a user for the 802.1x protocol. The RADIUS server that performs the authentication will inform the switch if this MAC can be registered in the MAC address table of switch.

Event log & message; 2 DI + 2 DO

In case of event, the IPGS-5408GSFP is able to send an email to pre-defined addresses as well as SNMP Traps out immediately. It provides 2DI and 2DO when disconnection of the specific port was detected; DO will activate the signal LED to alarm. DI can integrate the sensors for events and DO will trigger the alarm while sending alert information to IP network with email and traps.

Optional environmental monitoring for switch inside information (-M model)

The optional environmental monitoring can detect switch overall temperature, voltage, total PoE load and current where can send the SNMP traps and email when abnormal.

Dual DC powered input; Relay contact alarm, High ESD protection

The Lantech IPGS-5408GSFP is designed with dual power supply at 48VDC. Featured with relay contact alarm function, the IPGS-5408GSFP is able to connect with alarm system in case of power failure. The IPGS-5408GSFP also provides $\pm 2000V$ EFT and ± 4000 VDC (Contact) / ± 8000 VDC (Air) Ethernet ESD protection, which can reduce unstable situation caused by power line and Ethernet.

Industrial hardened design for extended temperature operation

Lantech IPGS-5408GSFP features high reliability and robustness coping with extensive EMI/RFI phenomenon, environmental vibration and shocks usually found in factory, substation, steel automation, aviation, mining and process control. It is the best solution for Automation, transportation, surveillance, Wireless backhaul, Semi-conductor factory and assembly lines.

The -E model can be used in extreme environments with an operating temperature range of -40°C to 75°C.


FEATURES & BENEFITS

- 8 10/100/1000T + 4 1000M SFP w/8 PoE 802.3af/at Injectors (Total 12 Ports Switch)
- Embedded 8 PoE Injectors IEEE802.3af/at function to feed power up to 30W@54V; 15W @ 48V per port for active operation
- PoE management including PoE detection and scheduling for PD (power devices)
- Back-plane (Switching Fabric): 24Gbps
- 16K MAC address table
- DDM to support SFP diagnostic function***
 - Automatically convert the raw data into dB
- values for TX power/RX power, making it easier to measure the fiber distance
- 10KB Jumbo frame
- User friendly UI, auto topology drawing, topology demo, complete CLI for professional setting
- Enhanced G.8032 Ring protection in 20ms < 256 switches
 - Support various ring/chain topologies, including train ring, enhanced ring, basic ring, auto ring & multiple VLAN ring
 - Enhanced G.8032 ring configuration with ease
 - Auto ring configuration (auto mode) for single


- ring
 - Cover multicast and data packets protection
- Dual DC input from 45V~56VDC
- Provides EFT protection ± 2000 VDC for power line.
- Supports ± 4000 VDC (Contact) and ± 8000 VDC (Air) Ethernet ESD protection
- Supports IEEE 802.1p Class of Service, per port provides 8 priority queues Port base, Tag Base and Type of Service Priority
- IEEE 802.1d STP, IEEE 802.1w RSTP, 802.1s MSTP VLAN redundancy with 16 MSTI.
- 4K 802.1Q VLAN, Port based VLAN, GVRP, QinQ, QoS
- Supports IEEE 802.1ab LLDP, Cisco CDP; LLDP info can be viewed via Web/ Console
- DHCP server / client / DHCP Option 82 relay / DHCP Option 82 server ; Port based DHCP server; DHCP Option 66; DHCP Snooping, basic IPv6 DHCP server
- Mac based DHCP server to assign IP address
- Bandwidth Control
 - Ingress packet filter and egress rate limit
 - Broadcast/multicast packet filter control
- Relay alarm output system events
- Miss-wiring avoidance
 - LED indicator
- Node failure protection
 - Ensure the switches in a ring to survive after power breakout is back
 - The status can be shown in NMS when each switch is back
- USB for edited restoration and auto backup
- System Event Log and SNMP Trap for alarm support; 32 RMON counters
- Security
 - SSL/SSH v2/INGRESS/EGRESS ACL L2/L3
 - MAC address table: MAC address entries/Filter/MAC-Port binding
 - TACACS+**
 - IP Security: IP address security management to prevent unauthorized intruder.
 - Login Security: IEEE802.1X/RADIUS
 - HTTPS for secure access to the web interface
- Static multicast forwarding forward reversed IGMP flow with multicast packets binding with ports for IP surveillance application
- IGMP router port to assign query in ring for reversed multicast video flow
- Multicast VLAN registration* for metro video
- IGMPv1,v2,v3 with Query mode for multimedia; GMRP**
- Factory reset button to restore setting to factory default
- Watchdog design to auto reboot switch CPU is found dead
- Environmental monitoring** for system input voltage, current ,total PoE load and ambient temperature (-M model)
- Supports 2DI / 2DO (Digital Input / Digital Output)
- IP30 metal housing with DIN rail and Wall-mount** design
- TFTP/ HTTP firmware upgrade
- MLD Snooping for IPv6 Multicast stream
- Diagnostic including Ping / DDM information
- Auto Provision to verify switch firmware with the latest or certain version
- Configuration backup and restoration
 - Supports editable configuration file for system quick installation
 - USB port for upload / download configuration by USB dongle

DIMENSIONS (unit=mm)

Standard model



-E model



SPECIFICATION

Hardware Specification

| | |
|-----------|---|
| Standards | IEEE802.3 10Base-T Ethernet IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T Ethernet IEEE802.3z Gigabit fiber IEEE802.3x Flow Control and Back Pressure IEEE802.3ad Port trunk with LACP IEEE802.1d Spanning Tree IEEE802.1w Rapid Spanning Tree IEEE802.1s Multiple Spanning Tree IEEE802.3ad Link Aggregation Control |
|-----------|---|

| | |
|---------------------|--|
| Protocol (LACP) | IEEE802.1AB Link Layer Discovery Protocol (LLDP) |
| Switch Architecture | IEEE802.1X User Authentication (Radius) |
| Transfer Rate | IEEE802.1p Class of Service |
| | IEEE802.1Q VLAN Tag |
| | IEEE802.3at/af Power over Ethernet |
| | Back-plane (Switching Fabric): 24Gbps |
| | 14,880pps for Ethernet port |
| | 148,800pps for Fast Ethernet port |
| | 1,488,000pps for Gigabit Ethernet / Gigabit Fiber port |

| | |
|-----------------------|--|
| Mac Address | 16K MAC address table |
| Jumbo frame | 10KB |
| Connectors | 10/100/1000T: 8 x ports RJ-45 PoE with Auto MDI/MDI-X function Mini-GBIC: 4 x 1000 SFP socket with DDM RS-232 connector: RJ-45 type USB for configuration restore/backup Power & Relay connector: 1 x 6-pole terminal block DIDO : 1 x 6-pole terminal block |
| Network Cable | 10Base-T: 2-pair UTP/STP Cat. 3, 4, 5/ 5E/ 6 cable EIA/TIA-568 100-ohm (100m) 100Base-TX: 2-pair UTP/STP Cat. 5/ 5E/ 6 cable EIA/TIA-568 100-ohm (100m) 1000Base-TX: 2-pair UTP/STP Cat. 5/ 5E/ 6 cable EIA/TIA-568 100-ohm (100m) |
| Optical Cable | 1.25Gbps: Multi mode: 0 to 550 m, 850 nm (50/125 μm); 0 to 2 km, 1310 nm (50/125 μm) Single mode: 0 to 10 km/ 30 km/ 40 km, 1310 nm (9/125 μm); 0 to 50 km/ 60 km/ 80km/ 120 km, 1550 nm (9/125 μm) WDM 1.25Gbps: Single mode: 0 to 10 km/ 20 km/ 40 km/ 60 km, 1310 nm (9/125 μm); 0 to 80 km, 1490 nm (9/125 μm); 0 to 10 km/ 20 km/ 40 km/ 60 km/ 80 km, 1550 nm (9/125 μm) |
| LED | Per unit: Power 1 (Green), Power 2 (Green), FAULT (Red) Ethernet port: Link/Activity (Green), Speed (Green); Mini-GBIC: Link/Activity (Green) R.M. indicator (Green) |
| DI/DO | 2 Digital Input (DI) : Level 0: -30~2V / Level 1: 10~30V Max. input current:8mA 2 Digital Output(DO): Open collector to 40 VDC, 200mA |
| Operating Humidity | 5% ~ 95% (Non-condensing) |
| Operating Temperature | -20°C~60°C / -4°F~140°F (Standard model) -40°C~75°C / -40°F~167°F(-E model) |
| Storage Temperature | -40°C~85°C / -40°F~185°F |
| Power Supply | 48VDC |
| PoE Budget | 240W for 45~56V input (50~56VDC input is recommended for 802.3at 30W applications) Higher PoE budget can be applied upon request. ** |
| PoE pin assignment | RJ-45 port # 1~ # 8 support IEEE 802.3at/af End-point. Per port provides up to 30W Positive (VCC+): RJ-45 pin 1,2. Negative (VCC-): RJ-45 pin 3,6. |
| Power Consumption | 10W |
| Case Dimension | Metal case. IP-30, 74(W) x 105 (D) x 152 (H) mm (Standard model) 96.3(W) x 105 (D) x 152 (H) mm (-E model) |
| Weight | 900 g |
| Installation | DIN Rail and Wall Mount** Design |
| EMI & EMS | FCC Class A, CE EN55032 Class A, CE EN55024, CE EN61000-4-2, CE EN61000-4-3, CE EN61000-4-4, CE EN61000-4-5, CE EN61000-4-6, CE EN61000-4-8, CE EN61000-6-2 |

| | |
|-------------------------------|--|
| | BS EN55032, BS EN55024, BS EN61000-4-2, BS EN61000-4-3, BS EN61000-4-4, BS EN61000-4-5, BS EN61000-4-6, BS EN61000-4-8 |
| Stability Testing | IEC60068-2-32 (Free fall), IEC60068-2-27 (Shock) IEC60068-2-64 (Vibration) |
| MTBF | 635,105 Hrs. (standards IEC62380) |
| Warranty | 5 years |
| Software Specification | |
| Management | SNMP v1 v2c, v3/ Web/Telnet/CLI |
| SNMP MIB | MIB MIBII SNMP MIB Bridge MIB IF MIB RMON MIB Private MIB |
| ITU G.8032 | Support ITU G.8032 v2/2012 for Ring protection in less than 20ms for self-heal recovery (single ring) Support various ring/chain topologies Includes train ring, auto ring, basic single ring, enhanced ring, multiple-VLAN ring Enhanced G.8032 ring configuration with ease. Protect multicast & unicast data |
| PoE Management | 1. PoE Detection to check if PD is hang up then restart the PD 2. PoE Scheduling to On/OFF PD upon routine time table |
| Per Port PoE Status | On/ Off, voltage, current, watts, temperature |
| User friendly UI | <ul style="list-style-type: none"> ■ Auto topology drawing ■ Topology demo ■ Auto configuration for G.8032(auto mode) for single ring ■ DDM threshold monitoring with dB values*** ■ Complete CLI for professional setting |
| Port Trunk with LACP | LACP Port Trunk: 8 Trunk groups |
| LLDP | Supports LLDP to allow switch to advise its identification and capability on the LAN |
| CDP | Cisco Discovery Protocol for topology mapping |
| Environmental Monitoring** | System status for input voltage, current , total PoE load and ambient temperature to be shown in GUI and sent alerting if any abnormal status (-M model) |
| VLAN | Port Based VLAN IEEE 802.1Q Tag VLAN (256 entries)/ VLAN ID (Up to 4K, VLAN ID can be assigned from 1 to 4096.) GVRP, QinQ, Protocol based VLAN ; IPv4 Subnet based VLAN |
| MLD Snooping | Support IPv6 Multicast stream |
| Spanning Tree | Supports IEEE802.1d Spanning Tree and IEEE802.1w Rapid Spanning Tree, IEEE802.1s Multiple Spanning Tree 16MSTI |
| Quality of Service | The quality of service determined by port / CoS / ToS / VLAN / 61375-3-4 |
| Class of Service | Support IEEE802.1p class of service, per port provides 8 priority queues |
| Login Security | Supports IEEE802.1X Authentication/RADIUS |
| Port Mirror | Support 3 mirroring types: "RX, TX and |

| | |
|------------------------|--|
| | Both packet" |
| Network Security | Support 10 IP addresses that have permission to access the switch management and to prevent unauthorized intruder. 802.1X access control for port based and MAC based authentication/MAC-Port binding Management access control with priority Ingress/Egress ACL L2/L3 SSL/ SSH v2 for Management HTTPS for secure access to the web interface TACACS+** for Authentication |
| IGMP | Support IGMP snooping v1,v2,v3; 1024 multicast groups; IGMP router port ; IGMP query; GMRP** |
| Static MAC-Port Bridge | Static multicast forwarding forward reversed IGMP flow with multicast packets binding with ports for IP surveillance application |
| Bandwidth Control | Support ingress packet filter and egress packet limit. The egress rate control supports all of packet type. Ingress filter packet type combination rules are Broadcast/Multicast/Flooded Unicast packet, Broadcast/Multicast packet, Broadcast packet only and all types of packet. The packet filter rate can be set an accurate value through the pull-down menu for the ingress packet filter and the egress packet limit. |
| Flow Control | Supports Flow Control for Full-duplex and Back Pressure for Half-duplex |
| System Log | Supports System log record and remote |

| | |
|-----------------------------------|--|
| | system log server |
| Relay Alarm | Provides one relay output for port breakdown, power fail and alarm. Alarm Relay current carry ability: 1A @ DC24V |
| Protection | <ul style="list-style-type: none"> ■ Miss-wiring avoidance ■ Node failure protection ■ Loop protection |
| SNMP Trap | Up to 10 trap stations; trap types including: <ul style="list-style-type: none"> ● Device cold start ● Authorization failure ● Port link up/link down ● DI/DO open/close ● Typology change(ITU ring) ● Power failure ● Environmental abnormal** |
| DHCP | Provide DHCP Client/ DHCP Server/DHCP Option 82/Port based DHCP; DHCP Option 66; DHCP Snooping, basic IPv6 DHCP server |
| Mac based DHCP Server | Assign IP address by Mac |
| Diagnostic | Support Ping and DDM information |
| DNS | Provide DNS client feature |
| SNTP | Supports SNTP v4 to synchronize system clock in Internet |
| Firmware Update | Supports TFTP firmware update, TFTP backup and restore; HTTP firmware upgrade |
| Configuration upload and download | Supports text configuration file for system quick installation; Support factory reset button to restore all settings back to factory default; USB port for upload/download configuration by USB dongle. |
| Auto Provision | To verify switch firmware with the latest or certain version |

*Future release

**Optional

***Optional DDM SFP required

ORDERING INFORMATION

- **IPGS-5408GSFP.....P/N: 8350-606**
8 10/100/1000T PoE at/af + 4 1000M SFP L2+ Industrial Managed Ethernet Switch w/USB; -20°C to 60°C
- **IPGS-5408GSFP-E.....P/N: 8350-607**
8 10/100/1000T PoE at/af + 4 1000M SFP L2+ Industrial Managed Ethernet Switch w/USB; -40°C to 75°C
- **IPGS-5408GSFP-M.....P/N: 8350-608**
8 10/100/1000T PoE at/af + 4 1000M SFP L2+ Industrial Managed Ethernet Switch w/ USB & Environmental monitoring; -20°C to 60°C
- **IPGS-5408GSFP-M-E.....P/N: 8350-609**
8 10/100/1000T PoE at/af + 4 1000M SFP L2+ Industrial Managed Ethernet Switch w/ USB & Environmental monitoring; -40°C to 75°C

OPTIONAL ACCESSORIES

DIN Rail Power

- **NDR-480 Series** 480W Single Output Industrial Din Rail Power; 90-264VAC / 127-370VDC Input Range; Cooling by free air convection; RoHS2 ; Operating Temp. -20°C~70°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C)
- **NDR-240 Series** 240W Single Output Industrial Din Rail Power; 90-264VAC / 127-370VDC Input Range; Cooling by free air convection; RoHS2 ; Operating Temp. -20°C~70°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C)
- **NDR-120 Series** 120W Single Output Industrial Din Rail Power; 90-264VAC / 127-370VDC Input Range; Cooling by free air convection; RoHS2 ; Operating Temp. -20°C~70°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C; For 115VAC, please refer to derating curve on NDR-120 Series datasheet)
- **NDR-75 Series** 75W Single Output Industrial Din Rail Power; 90-264VAC / 127-370VDC Input Range; Cooling by free air convection; RoHS2 ; Operating Temp. -20°C~70°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C; For 115VAC, please refer to derating curve on NDR-120 Series datasheet)

Mini GBIC (SFP)

| | | | |
|----------------|--|---------------|---|
| ■ 8330-162-V1 | MINI GBIC 1000SX (LC/MM/0.5KM) Transceiver | ■ 8330-196-V1 | 1.25Gbps BiDi SFP 2KM Transceiver (WDM 1550) |
| ■ 8330-163-V1 | MINI GBIC 1000SX2 (LC/MM/2KM) Transceiver | ■ 8330-188-V1 | 1.25Gbps BiDi SFP 10KM Transceiver (WDM 1310) |
| ■ 8330-165-V1 | MINI GBIC 1000LX (LC/SM/10KM) Transceiver | ■ 8330-189-V1 | 1.25Gbps BiDi SFP 10KM Transceiver (WDM 1550) |
| ■ 8340-0591-V1 | MINI GBIC 1000LHX (LC/SM/40KM) Transceiver | ■ 8330-186-V1 | 1.25Gbps BiDi SFP 20KM Transceiver (WDM 1310) |
| ■ 8330-166-V1 | MINI GBIC 1000XD (LC/SM/50KM) Transceiver | ■ 8330-187-V1 | 1.25Gbps BiDi SFP 20KM Transceiver (WDM 1550) |
| ■ 8330-169-V1 | MINI GBIC 1000XD (LC/SM/60KM) Transceiver | ■ 8330-180-V1 | 1.25Gbps BiDi SFP 40KM Transceiver (WDM 1310) |
| ■ 8330-167-V1 | MINI GBIC 1000ZX (LC/SM/80KM) Transceiver | ■ 8330-182-V1 | 1.25Gbps BiDi SFP 40KM Transceiver (WDM 1550) |
| ■ 8330-170-V1 | MINI GBIC 1000EZ (LC/SM/120KM) Transceiver | ■ 8330-181-V1 | 1.25Gbps BiDi SFP 60KM Transceiver (WDM 1310) |
| ■ 8330-168-V1 | MINI GBIC 10/100/1000T (100m) Transceiver | ■ 8330-183-V1 | 1.25Gbps BiDi SFP 60KM Transceiver (WDM 1550) |
| ■ 8330-197-V1 | 1.25Gbps BiDi SFP 0.5KM Transceiver (WDM 1310) | ■ 8330-184-V1 | 1.25Gbps BiDi SFP 80KM Transceiver (WDM 1490) |
| ■ 8330-198-V1 | 1.25Gbps BiDi SFP 0.5KM Transceiver (WDM 1550) | ■ 8330-185-V1 | 1.25Gbps BiDi SFP 80KM Transceiver (WDM 1550) |
| ■ 8330-195-V1 | 1.25Gbps BiDi SFP 2KM Transceiver (WDM 1310) | | |

All SFP# ended with D are with DDM function

Wall Mount Bracket

| | |
|------------------|---|
| MBAK19003 | Wall mount bracket for 74(W) x 105 (D) x 152 (H) mm / 96 (W) x 105 (D) x 152 (H) mm Industrial switches |
| MBAK19004 | 19" Rack Mounting Kit for 74x105x152mm/74x135x152mm Industrial Switch |

Lantech Communications Global Inc.

www.lantechcom.tw
 info@lantechcom.tw

© 2024 Copyright Lantech Communications Global Inc. all rights reserved.
 The revise authority rights of product specifications belong to Lantech Communications Global Inc.
 Lantech may make changes to specification and product descriptions at anytime, without notice.